



NOTES:

1. CLEARING AND GRUBBING WITHIN THE DRIPLINE OF TREES TO BE PRESERVED, SHALL BE LIMITED TO SURFACE CLEARING AND GRUBBING TO A MAXIMUM DEPTH OF 2 INCHES USING HAND TOOLS.
2. EROSION CONTROL BLANKET MAY BE PLACED ON UNDISTURBED SOIL WITH MAXIMUM OF 1 1/2" MOWED PLANT STUBBLE.

INSTALL 6" LONG SOD STAMPLE AT EACH CORNER AND 2' O.C. ALONG OUTER EDGE

TREE TRUNK

TWO LAYER EROSION CONTROL BLANKET (COCO FIBER ON BOTTOM AND ENKAMAT ON TOP) TRIMMED, CUT AND SLIT TO FIT AROUND TREE.

SHOREBLOCK® MAT

EXISTING GRADE

LIMIT OF GRADING

3'-0"

3'-0"

LIMIT OF GRADING

**SHORETEC® L.L.C.**

510 O'NEAL LANE  
Baton Rouge, Louisiana 70819  
(225) 408-1444 - Phone  
(225) 408-1445 - Fax  
www.shoretec.com

Client:

Scale:  
N.T.S.

Drawn By:  
A. CASE

File Name:

Title:

SHOREBLOCK® SD SERIES  
SCOUR PROTECTION AT TREES

Project No:

Drawing No:  
24

No.	Date	Revision	By

DISCLAIMER  
THE INFORMATION CONTAINED HEREIN HAS BEEN COMPILED BY SHORETEC® LLC AND TO THE BEST OF OUR KNOWLEDGE, ACCURATELY REPRESENTS THE SHOREBLOCK® PRODUCT USE IN THE APPLICATIONS WHICH ARE ILLUSTRATED. FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND ITS MANNER OF USE ARE THE SOLE RESPONSIBILITY OF THE USER. STRUCTURAL DESIGN AND ANALYSIS SHALL BE PERFORMED BY A QUALIFIED ENGINEER.

THIS DRAWING IS BEING FURNISHED FOR THIS SPECIFIC PROJECT ONLY. ANY PARTY ACCEPTING THIS DOCUMENT DOES SO IN CONFIDENCE AND AGREES THAT IT SHALL NOT BE DUPLICATED IN WHOLE OR IN PART, NOR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF SHORETEC® L.L.C.